

Fixing of cow mattresses on concrete with the Z2-Lathnail (stainless steel)

immovable, simple and fast fixing!

Working method:

Drill a hole of 5 mm into the concrete for nails with diameter 5 mm.

Drill a hole of 6 mm into the concrete for nails with diameter 6 mm.

Hit the nail with a hammer into the pre-drilled hole.

The Z2 nail will pull the mattress tightly against the surface.



Zandvoort
Draadindustrie B.V.
factory of specialty nails



Special characteristics of the Z2-lath nails:

- * made of stainless steel, quality AISI-304/1.4301/V2A
- * no sharp edges because of the flattened bombée head
- * special helical grooves rolled into the shank
- * mechanical zinc plated with min. 10 micron zinc
- * high pull out forces and high shearing values
- * no plastic plugs (environmentally friendly and fire resistant)

The Z2-Lath nail is also available in
hardened steel, hardness min. 50 HRc.
Mechanical zinc plated with min. 10
micron zinc.

Technical information	concrete (B-55)	concrete (B-55)
nail size	6,5 x 60 mm	5,5 x 60 mm
hole diameter	6 mm	5 mm
hole depth	aprox. 60 mm	aprox. 50 mm
nail depth	40 mm	40 mm
pull out force	970 kg	790 kg

